



#### **PARETE LENS**

- Arkilight Parete Lens designed with a monoblock lens optic to provide grazing effect
- $^{\circ}\,$  To be configured with monochrome LED light sources
- ° Flexible modularity with linear alignment accessories
- ° Adaptable profile for cabling (Canalina) in order to run connector and cable through a secondary space
- $^{\circ}\,$  Lens optics with narrow beam light distribution
- $^{\circ}\,$  Optimum heat dissipation performance for high lumen LED strips and LED modules
- $^{\circ}\,$  High quality aluminium alloy with premium anodized finish
- $^{\circ}\,$  Various finishing options such as anodizing and customized RAL finishing
- $^{\circ}\,$  Parete Lens LED profiles configured with dedicated accessories, mounting brackets and end caps



PARETELENS\_H18















#### **PRODUCT FEATURES**

#### Technical Data

Mounting Type	Surface Mounted Ceiling
	Surface Mounted Wall
	Surface Mounted Floor
	Suspended
Profile Trim Type	With Trim
Light Distribution	Narrow Beam Lens
Optic Type	Lens Grazer
Bending Options	Non - Bendable
Material	Aluminum 6060/6063
Cooling Capacity	30 W/m
Led Path Width	13 mm
IP Protection	IP20

#### Finish/Colour

Anodized Matte Finish Matte Light Gray Anodized

## **Light Distribution**

Narrow Beam Lens

### **Mounting Type**

Surface Mounted Ceiling	$\checkmark$
Surface Mounted Wall	J
Surface Mounted Floor	J
Suspended	$\checkmark$

## Profile Trim Type

With Trim

# **Application Type**

Graze Lighting

## Optic Type

Lens Grazer  $\sqrt{\phantom{a}}$